

Performance



15 Litres
60-75 m²
2 coats

12.5 Litres
50-62 m²
2 coats

4 Litres
16-20 m²
2 coats

1 Litre
4-5 m²
2 coats

Main features

DRYING (between coats)	30 minutes
DRYING (polishing by hand)	30 - 40 minutes
DRYING (machine polishing)	90 minutes
APPLICATION TOOLS	Stucco trowel, Japanese finishing trowels, electric polisher (optional).
TOOLS CLEANING	Water
FINISH	Marble / Glossy

Transform your **HOME** into a **TREE** by painting with **GRAPHENSTONE***



*Three 15 litre buckets of our paint absorbs more than 10Kg of CO₂. This is the same amount an adult tree weighing 250Kg would absorb in one year.

More information at:
www.myhomeisatree.com



World's
Most Certified
Green Brand



More than 13
National & International
Awards

PAINTS FOR THE
green
GENERATION

GRAPHENSTONE
THE ORIGINAL & AUTHENTIC

Graphenstone Headquarters | IEdiSA, S.A.
Polg Ind Poliviso. Carpinteros, 25.
41520 El Viso del Alcor, Seville. España (Spain).
Phone: (+34) 955 529 435
info@graphenstone.com
www.graphenstone.com

IEdiSA, SA. © Copyright 2019. All rights reserved.

GRAPHENSTONE

THE ORIGINAL & AUTHENTIC

Stuki Premium

NATURAL COATING WITH GRAPHENE
VENETIAN STUCCO



www.graphenstone.com

GRAPHEN
STONE

Discover *Stuki*
now in **COLOURS***

*Colours available upon request.
Check for availability.

ColorSystem

322
EXTERIOR



GRAPHE
STO

ColorSyste

980
INTERIOR

Stuki

Premium

Stuki is a decorative **natural coating** that you can achieve a "**Venetian stucco**" finish easily.

A versatile, durable and ecological product. Thanks to its **breathable natural base**, it allows you to decorate in a healthier way creating classic or contemporary spaces.

Thanks to its formula with **graphene technology**, it is more resistant, so you can also decorate **exterior walls**.

White

Colour



Easy to apply



PREPARATION

Shake component A (liquid) and slowly add component B (solid) stirring until a uniform paste is obtained.



APPLICATION

1. Apply a first coat to the support with a metal trowel. Let dry 20-30 minutes.



2. Lightly sand the support to eliminate any irregularity before applying the second layer.



3. Apply a second layer with a metallic trowel making the desired drawing (for example: marbling). Let dry 20-30 minutes.



FINISH

For the finishing, make semi-circular movements with a stucco trowel (or Japanese trowel) until obtaining the desired brightness.



If the product has dried, it is recommended to use a spray bottle with water to moisten the support and continue finishing the product.

